Product datasheet

Specifications



Rack PDU, Metered, 1U, 16A, 208/230V, (8) C13



AP7821B

Overview

Lead Time Usually in Stock	
----------------------------	--

Main

Pdu Type	Metered
Cord Length	2.50 m
Provided Equipment	Cord retention bracket(s) Installation guide Rack mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	4.4 cm
Width	44.4 cm
Output Voltage	208 V 230 V
Depth	10.2 cm
Net Weight	1.74 kg
Mounting Location	Front Rear
Mounting Preference	No preference
Input Plug Type	IEC 60320 C20
Mounting Mode	Rack-mounted
Rack Units	1U
Mounting Position	Horizontal
[In] Rated Current	16 A
Input Current Limits	20 A
Load Capacity	3300 VA
Network Frequency	50/60 Hz
Total Number Of Outlets	8 IEC 60320 C13

Environment



Product Certifications	cUL listed C-Tick CE CSA GOST UL listed VCCI
Standards	FCC part 15 class A ICES-003 UL 60950
Ambient Air Temperature For Operation	-545 °C
Relative Humidity	595 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %
Storage Altitude	0.0015240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	33.7 cm
Package 1 Length	47 cm
Package 1 Weight	2.92 kg

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

23-Apr-2024

Rohs Exemption Information

/es

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information