

Product datasheet

Specifications



Power Cord, Locking C19 to C20, 3.0m



AP8760

Overview

Presentation Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

Lead Time Usually in Stock

Main

Input Connection Type IEC 60320 C20

Cable Length 3.05 m

Number Of Cables 1

Physical

Colour Black

Height 23 cm

Width 23 cm

Depth 4.5 cm

Net Weight 0.51 kg

Mounting Preference No preference

Mounting Mode Not rack-mountable

Input

Max Line Current 16 A

Output

Max Current Draw 16 A

Number Of Power Socket Outlets 1 IEC 60320 C19

Power Cable Length 3.05 m

Conformance

Product Certifications CCC
CSA
PSE
UL listed
VDE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient Air Temperature For Operation	0...75 °C
Relative Humidity	20...80 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage Altitude	0.00...15240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	23 cm
Package 1 Width	23 cm
Package 1 Length	4.5 cm
Package 1 Weight	0.51 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)