



Build secure IT environments,
Faster. Simpler. Smarter.

Presenting the Flexibox Enclosure

This range of wall mount cabinets from Schneider Electric President System Ltd is ideal for the modern office environment.

Flexibox range is supplied as a complete knockdown kit that can be assembled at the site in 10 minutes. Top and bottom cable entry provide optimal flexibility for cable management.



Life Is On

Schneider
Electric

Features

Why your IT equipment needs the Flexibox?



Compatibility

Flexibox cable and accessory integration	The bottom and roof of the Flexibox have easy-to-remove knock outs. These knocks can be used for cable entry/exits.
Vendor-neutral EIA-310 19in Rack Mounting Compatible	Assured compliance with all the EIA-310-E mount equipment provides peace of mind as they physically fit in a Flexibox

Safety

Robust Design	Bolted CRCA steel construction provides load bearing capacity up to 40kgs (88.18 pounds)
Integrated electrical grounding	All the wall mount components are electrically connected with a single point for grounding.

Convenience

Cable access openings with gland plates	Fans at top and vents in the bottom ensures uniform delivery of cool air to installed IT equipment's.
Simple selection	Flexibox can be supplied in CKD flat pack condition for ease of handling. Bolted construction ensures ease of assembly at site.
Equipment mounting rails	Quick release front toughened clear glass door provides visibility of installed equipment's.

Life Is On

Schneider
Electric

Technical Specifications

SKU No.	FLX-65-CKD	FLX-95-CKD	FLX-125-CKD	FLX-155-CKD	FLX-66-CKD	FLX-96-CKD	FLX-126-CKD	FLX-156-CKD
Type (CKD / Assembled)	CKD	CKD	CKD	CKD	CKD	CKD	CKD	CKD
Physical								
Height (U)	6U	9U	12U	15U	6U	9U	12U	15U
Net Weight (Kg) ± 5kg	13	15	18	21	16	18	21	24
Maximum Height (mm)	360	495	625	760	360	495	625	760
Maximum Width (mm)	550	550	550	550	550	550	550	550
Maximum Depth (mm)	500	500	500	500	600	600	600	600
Shipping Weight (Kg)	14	16	19	22	17	19	22	25
Shipping Height (mm)	220							
Shipping Width (mm)	530		570		630		600	
Shipping Depth (mm)	580		640	775	580		640	775
Color	Grey							
Maximum Mounting Depth (mm)	350				450			
Minimum Mounting Depth (mm)	50							
Panels (Gauge)	21							
Vertical Post (19" Angles) (Gauge)	16							
Weight Capacity (static load) (Kg)	40							
Environmental								
Protection Class	IP20							
Conformance								
Standard Warranty	1 year							
Sustainable Offer Status								
ROHS	Compliant							
REACH	Contains No SVHCs							

Wallmount, Front glass door, shelf, Fan, Front panel H/w, Earthing Kit and PDU 230V AC (6X5)

Life Is On



Life Is On



schneiderelectricpresident.com



Schneider Electric President Systems **Ltd.**
Plot No 5C/1, KIADB Industrial Area,
Attibele, Bangalore - 562107
Email id: info@schneiderelectricpresident.com