

# Product datasheet

Specifications



## APC Back-UPS 600VA, 230V without auto shutdown software, 3 India outlets

BX600C-IN

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	360 W
Rated Power In Va	600 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Output Connection Type	3 India 3-pin 6A
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Number Of Battery Replacement Quantity	1
Battery Voltage	12 V
Battery Graph Comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended Runtime	0
Replacement Battery	<a href="#">RBC2</a>

### General

Provided Equipment	user manual
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

## Physical

Colour	Black
Height	21.8 cm
Width	10.7 cm
Depth	23.7 cm
Net Weight	4.7 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	45...65 Hz auto-sensing
Plug Standard	India 3-pin 6A
Input Voltage Limits	145...290 V

## Output

Maximum Configurable Power In W	360 W
Output Frequency	50 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Full Load Runtime	360 W
Maximum Configurable Power In Va	600 VA
Transfer Time	10 ms typical : 12 ms maximum

## Conformance

Product Certifications	BIS
------------------------	-----

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0...15000 m
Acoustic Level	45 dBA

## Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and building wiring fault
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

---

Surge Energy Rate 255 J

## Packing Units

---

Unit Type Of Package 1 PCE

---

Number Of Units In Package 1 1

---

Package 1 Height 29.5 cm

---

Package 1 Width 31 cm

---

Package 1 Length 16.5 cm

---

Package 1 Weight 5.2 kg

## Contractual warranty

---

Warranty 2 years repair or replace

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

Energy Efficient Product

---

Take-Back Program Available

---

## Well-being performance

Mercury Free

---

Rohs Exemption Information Yes

---

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant with Exemptions

---

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

**Circularity Profile** [End of Life Information](#)

---